

Conformal Coating Remover

2510

Techspray offers a variety of coating formulas to match field and engineering requirements. Specifications generally depend on the type of protection needed: e.g. thermal, moisture, and static resistance.

Coatings contain Opti/Scan to allow quality control inspection of coverage and evenness of the coating on a PCB. A coated board can be passed under a standard, low-cost UV (short-wave black) light, and the coated areas glow. The brighter the glow, the thicker the coating.





Coating Stripper for Acrylic, Silicone & Urethane

Quickly and precisely removes most conformal coatings including acrylic, urethane, and silicone.

- · Fast stripping action
- Non-corrosive
- · Non-ozone depleting
- Rapid evaporation

Product Packaging

2510-P Conformal Coating Remover 1 pt 2 units/case







Technical Information

Chemical & Physical Properties

Appearance	Clear, colorless iquid
Odor	Aromatic odor
Flash Point	-14.4°C (6°F)
VOC (EPA)	886.000 to 891 g/L
Boiling Point	to 65°C (149°F)

Chemical Composition

CHEMICAL NAME	CAS#
Tetrahydrofuran	109-99-9
ВНТ	128-37-0

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America Techspray P.O. Box 949 Amarillo, TX 79105 800-858-4043

Email: tsales@techspray.com

Europe
ITW Contamination Control
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400

Email: info@itw-cc.com

Countries Outside US
Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2014 Techspray, A Division of ITW

